



CONIATO DUREZZA 59 - 63 HRC - TORSION

 Articolo		LUNG. mm	Descrizione	
12060	PZ 1	25	INSERTO ATT.1/4"C PZ1 L.25	1
12060B	PZ 1	25	BOX INSERTI ATT.1/4"C PZ1 L.25	200
12060BX	PZ 1	25	BOX INSERTI ATT.1/4"C PZ1 L.25	500
12060BXL	PZ 1	25	BOX INSERTI ATT.1/4"C PZ1 L.25	1000
12061	PZ 2	25	INSERTO ATT.1/4"C PZ2 L.25	1
12061B	PZ 2	25	BOX INSERTI ATT.1/4"C PZ2 L.25	200
12061BX	PZ 2	25	BOX INSERTI ATT.1/4"C PZ2 L.25	500
12061BXL	PZ 2	25	BOX INSERTI ATT.1/4"C PZ2 L.25	1000
12062	PZ 3	25	INSERTO ATT.1/4"C PZ3 L.25	1
12062B	PZ 3	25	BOX INSERTI ATT.1/4"C PZ3 L.25	200
12062BX	PZ 3	25	BOX INSERTI ATT.1/4"C PZ3 L.25	500
12062BXL	PZ 3	25	BOX INSERTI ATT.1/4"C PZ3 L.25	1000

Caratteristiche

CONIATO DUREZZA 59 - 63 HRC - TORSION

attacco: DIN 3126, C 6,35

impronta: DIN 5260, PZ