



CHIAVI A BUSSOLA A MACCHINA

Koken Articolo	mm	LUNG. mm	Diametro	Descrizione	
16410M-16	16	50	28,8	CHIAVE BUSS.SURF.DRIVE 3/4" 16 MM L.50 KOKEN	1
16410M-17	17	50	30	CHIAVE BUSS.SURF.DRIVE 3/4" 17 MM L.50 KOKEN	1
16410M-18	18	50	31,3	CHIAVE BUSS.SURF.DRIVE 3/4" 18 MM L.50 KOKEN	1
16410M-19	19	50	32,5	CHIAVE BUSS.SURF.DRIVE 3/4" 19 MM L.50 KOKEN	1
16410M-21	21	50	35	CHIAVE BUSS.SURF.DRIVE 3/4" 21 MM L.50 KOKEN	1
16410M-22	22	50	36,3	CHIAVE BUSS.SURF.DRIVE 3/4" 22 MM L.50 KOKEN	1
16410M-24	24	50	38,8	CHIAVE BUSS.SURF.DRIVE 3/4" 24 MM L.50 KOKEN	1
16410M-27	27	50	42,5	CHIAVE BUSS.SURF.DRIVE 3/4" 27 MM L.50 KOKEN	1
16410M-30	30	50	46,3	CHIAVE BUSS.SURF.DRIVE 3/4" 30 MM L.50 KOKEN	1
16410M-32	32	50	48,8	CHIAVE BUSS.SURF.DRIVE 3/4" 32 MM L.50 KOKEN	1
16410M-33	33	50	50	CHIAVE BUSS.SURF.DRIVE 3/4" 33 MM L.50 KOKEN	1
16410M-36	36	50	53,8	CHIAVE BUSS.SURF.DRIVE 3/4" 36 MM L.50 KOKEN	1

Caratteristiche

CHIAVI A BUSSOLA A MACCHINA BOCCA SURFACE DRIVE